



量程(kg)	10~250	300,500
D(mm)	φ8.2	φ10.2

技术参数

额定载荷 Rated load	kg	10, 20, 30, 40, 50, 75, 100, 150, 200, 250, 300, 500
灵敏度 Sensitivity	mV/V	2.0±0.002
综合误差 Total error	%F.S	±0.03
蠕变(30分钟) Creep(30min)	%F.S	±0.02
零点平衡 Zero balance	%F.S	±1
零点温度影响 TC ZERO	%F.S/10℃	±0.02
输出温度影响 TC SPAN	%F.S/10℃	±0.02
输入阻抗 Input resistance	Ω (ohms)	400±20
输出阻抗 Output resistance	Ω (ohms)	352±3
绝缘电阻 Insulation resistance	MΩ	≥5000
额定温度 Nominal Temp Range	℃	-10~+40
工作温度范围 Service Temp Range	℃	-30~+70
安全过载 Maximum safe overload	%F.S	150
极限过载 Ultimate overload	%F.S	200
推荐激励电压 Recommend excitation	V DC	10~12
最大激励电压 Maximum excitation	V DC	15
密封等级 Protection Class	Ip67	
材质 Construction	合金钢 Alloy Steel 不锈钢 Stainless Steel	
电缆 Cable	长度 Length: 3m 直径 Diameter: Ø5mm	

						宁波柯力传感科技股份有限公司			
						HSX10kg~500kg型-A(-ASS) 安装图			
设计			标准化			图样标记	重量	比例	
校对			会签			A			
审核			审定						
工艺			批准						
						共张 第张			
						KL/JT-HSX10kg~500kg型-A(-ASS). 0A			